

Features

Display Technology	1.3 in. polysilicon active matrix TFT x 3
Native Resolution	XGA (1024 x 768)
Resolution Supported	VGA (640 x 480), SVGA (800 x 600), SXGA (1280 x 1024), Mac 13", Mac 16"
Brightness	3200 ANSI Lumens
Contrast Ratio	250:1
Computer Compatibility	IBM PC or compatibles, Apple Macintosh
Compatibility	NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, HDTV (480i, 480p, 625i, 720p, 1035i, 1080i)
Aspect Ratio	4:3, supports 5:4, 16:9
Number of Colors	16.7 million
Input Sources	Computer: 2RGB (HD-15), DVI, 2 Stereo audio (mini-jack) Video: Composite Video (RCA), S-Video (mini-DIN), Component Video (RCA), Audio (RCA x 2)
Output	RGB (HD-15), Audio (mini-jack)
Control	Mouse (PS/2, USB, Serial), RS-232
Keystone Correction	95% optical offset, +/- 20 degrees digital
Projection Options	Front/rear, desktop/ceiling
Audio	2 x 1.2-watt stereo
Remote Control	Full-featured remote with mouse control and laser pointer

Standard Lens

Projection Lens	F: 1.7 - 2.3 f = 49-64 mm
Throw Ratio	1.8 to 2.4:1

Image Size (in.)			Throw Distance (ft.)	
Diagonal	Width	Height	Min.	Max.
40	32	24	4.8	6.4
60	48	36	7.2	9.6
80	64	48	9.6	12.8
100	80	60	12	16
120	96	72	14.4	19.2
150	120	90	18	24
200	160	120	24	32

MCSi, Inc. Headquarters
 4750 Hempstead Station Drive
 Dayton, Ohio 45429
 Tel. (800) 875-5211
 Web Site: mcsinet.com
 For information on other MCSi products: 800-516-0600



MC-X3200



Technical

H-Sync Range	15 - 100 kHz
V-Sync Range	43.5 - 130 Hz
Bandwidth	135 MHz
Horizontal Resolution	500 TV lines
Lamp (Life)	250 watt UHB (2000 hours)
Dimensions	11.4" (W) x 13.8" (L) x 4.9 (H) 289 mm (W) x 350 mm (D) x 124 mm (H)
Weight	14.1 lbs. (6.4 kg)
Power Consumption	400 watts
Power Requirements	100 - 120V/220 - 240V 50/60 Hz
Operating Temperature	32° to 95°F (0°-35°C)
On-Screen Menu Languages	English, French, Norwegian, Italian, German, Dutch, Spanish, Portugese
Audible Noise	<40dB
Approvals	CE, UL, cUL, TUV, FCC Class B
Security	Kensington lock compatible
Warranty	Three years limited parts and labor (90-day lamp warranty, 1-year temporary replacement program).

Accessories

• Spare Lamp	250 watt UHB (2000 hours) (part no. MCX3200LAMP)
• Long Throw Zoom Lens (LL-301)	Throw Ratio = 4.73 to 6.2:1
• Wide Angle Zoom Lens (WL-201)	Throw Ratio = 1.43 to 1.9:1
• Cases (JEL-1511RP)	Padded wheeled Hard Case with Extension Handle
• Ceiling Mount (RPA 860)	Ceiling Mount Kit

©2001 MCSi, inc. All rights reserved. The MCSi & Radiant logo are registered trademarks of MCSi. All other trademarks contained in this document are the property of their respective owners. MCSi reserves the right to alter pricing, specifications and terms without notice at anytime.



11/01 D-VCG-1000-018

Portable projectors

MC-X3200



Ultrabright 3200 Lumens

True XGA 1024 x 768
resolution

Digital keystone correction

Power Zoom and Focus

2 RGB inputs, DVI Input,
3 Video Inputs, RGB Output

