

	DLP Series		
ASK Proxima Model	A1275	A2270	A2275
MP Schedule	Dec-11	Mar-12	Mar-12
Photo			
Display Technology	TI DLP (0.55" DMD)	TI DLP (0.55" DMD)	TI DLP (0.55" DMD)
Display Panel Type	DDP2431	DDP2431	DDP2431
Display Panel	1×0.55"	1×0.55"	1×0.55"
Marketing Brightness (Ansi Lumens)	2 700	2 700	2 700
Native Resolution	SVGA(800x600)	1024*768(XGA)	1024*768(XGA)
Contrast Ratio (Marketing)	2500:1	2500:1	2500:1
Projection Lens	1.1X Manual Zoom / Focus Lens	1.1X Manual Zoom / Focus Lens	1.1X Manual Zoom / Focus Lens
Uniformity (Marketing)	85%	85%	85%
Throw ratio	80"@3.2m	80"@3.2m	80"@3.2m
Throw Distance	1.5m-7m (40"-177")	1.5m-7m (40"-177")	1.5m-7m (40"-177")
Aspect Ratio	4:3(Standard) / 16:9(Compatible)	4:3 (Standard)/16:9(Compatible)	4:3 (Standard)/16:9(Compatible)
Keystone	Auto Keystone ±40°	Auto Keystone:±40°	Auto Keystone:±40°
Input	VGA*1 / S-Video*1 / Video*1/Audio In(Mini Jack)	VGA*2;S-video*1;Video*1; Audio-in*1(mini jack) ;RCA(L/R)*1;	VGA*2;S-video*1;Video*1; Audio-in*1(mini jack) ;RCA(L/R)*1; HDMI*1
Output	Audio Out(Mini Jack)	Audio-out*1(mini jack);VGA*1	Audio-out*1(mini jack);VGA*1
Control	RS232, USB- B slot	RS232;USB-B*1	RS232;USB-B*1, RJ45
PC Compatibility	VGA, SVGA, XGA, SXGA,WXGA,UXGA,Mac	VGA, SVGA, XGA, SXGA, WXGA, UXGA, MAC	VGA, SVGA, XGA, SXGA, WXGA, UXGA, MAC
Video Compatibility	PAL, SECAM,NTSC 4.43,PAL-M,N	PAL, SECAM, NTSC 4.43, PAL-M, N	PAL, SECAM, NTSC 4.43, PAL-M, N
Lens Shift H	No		
Lens Shift V	No		
Lamp	190W	190w	190w
Lamp Life (Marketing)	(Normal)4000H/(Eco)6000H	(Normal)4000H/(Eco)6000H	(Normal)4000H/(Eco)6000H
Remote Control	Yes	Yes	Yes
H-Synch Range	15-100 KHz	15-100 KHz	15-100 KHz
V-Synch Range	50-80 Hz &120HZ (3D)	50-80 Hz &120 HZ (3D)	50-80 Hz &120 HZ (3D)
Standby Power	<1W	<1w	<1w
Power Consumption	250W	250W	250W
Power Supply	100V – 240V @ 50-60 HZ	100V – 240V @ 50-60 HZ	100V – 240V @ 50-60 HZ
Operating Temp.	0-40℃	0-40℃	0-40℃
Store Temp.	-10℃-60℃	-10-60℃	-10-60℃
OSD Languages	16languages:Chinese,English,French,Spanish,Portuguese,German,Italian,Japanese, Russian,Dutch,Thai,Vietnam,Turkish,Africaans,Indonesian,Arabic	16 languages: Chinese,Japanese,Vietnam, English,German, French, Italian, Spanish, Portuguese, Dutch, , Russian, Thai, Indonesian, Arabic, Turkish,Africaans	16 languages: Chinese,Japanese,Vietnam, English,German, French, Italian, Spanish, Portuguese, Dutch, , Russian, Thai, Indonesian, Arabic, Turkish,Africaans
Speaker	2*3W	2*3W	2*3W
Dimension	273mm x 222.5mm x 92.5mm	273mm x 222.5mm x 92.5mm	273mm x 222.5mm x 92.5mm
Weight	≅ 2.5kg	≅ 2.5kg	≅ 2.5kg
Standard Accessories	User Manual(CD),Remote Control with Battery, Power Cord, VGA Cable, Warranty Card,Qualified card	User Manual (CD), Power Cord, Remote Control & battery, VGA Cable, Warranty Card, Qualified card	User Manual (CD), Power Cord, Remote Control & battery, VGA Cable, Warranty Card, Qualified card
Other Features	1. DLPLink for 3D Projection 2. Auto Rotate when mounted in ceiling 3. Auto Power-Off when no signal input 4. Auto Synch. 5. Auto Detection of Input Source 6. Blank Screen with one hotkey 7. Triple Password Protection 8. Image Freezing, Zoom & Panning	1. DLPLink for 3D Projection 2. Auto Rotate when mounted in ceiling 3. Auto Power-Off when no signal input 4. Auto Synch. 5. Auto Detection of Input Source 6. Blank Screen with one hotkey 7. Triple Password Protection 8. Image Freezing, Zoom & Panning	1. DLPLink for 3D Projection 2. Auto Rotate when mounted in ceiling 3. Auto Power-Off when no signal input 4. Auto Synch. 5. Auto Detection of Input Source 6. Blank Screen with one hotkey 7. Triple Password Protection 8. Image Freezing, Zoom & Panning