

Avio MP 200



AVIO MP 200



Brief Introduction

Beta 2.5

The MP 200 LCD projector from Avio has 550 Ansi lumens and an SVGA 800 x 600 resolution. The projector will be able to illuminate an image width of 204 cm well. However, if room light is available, the picture width should ideally not exceed 136 cm. The projector is no longer sold by the manufacturer. Unfortunately, we can no longer offer replacement lamps for this model, neither originals nor replicas.

3 x 1,3" LCD TFT Panel
SVGA 4/3 Liquid Crystal Display

Display Type

Ansi-Lumen

Contrast

Black Level

Offset

Resolution

Video Modes

Application

Light Source

Light Life

Operating Costs

Focus

Zoom

Objective

Throw Ratio

Audio

Connections

Ceiling Mounting

Power

Size WxHxD

Operating Noise

550

-

-

-

SVGA 800 x 600

480.000 Pixel

XGA 1024 x 768 compressed

NTSC, PAL, SECAM,

Stationary | Permanent installation in the training room and meeting room as well as the conference room.

Very narrow picture width and rooms with very little light.

150W Metalldampf Lamp

Articel Nr.: MPLK-C1

2000 h.

-

Manual

No Zoom

F=2,5 f=50mm

1,89:1

2 x 1W

Cinch Video in

S-Video in

D-sub 15pin in und out

Mini Jack in

Mikrofon in

Nein

260W

462 x 242 x 418 mm (18,2"x9,5"x16,5") 46,73 L/dm³

-

13,80 kg / 30,42 lbs.

-

Illumination

85%

Frequenz

H-sync: 15-57 kHz

V-sync: 50-75 Hz

Foot-Lamberts

17 fL / max. 204 cm screen width

58 cd/m²

Features

■ 1/2 inch CCD camera (color consecutive RGB filter system)

Projector

Screen 178 Lux (bei 203 cm Screen)

-

-

-



More Details



HCinema

<https://www.projector-database.com/pro/aviomp200-en.html>

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.