

CP745e



BRIGHTNESS

2600 ANSI lumens

RESOLUTION

1024 x 768 XGA

1280 x 1084 SXGA
compressed

DISPLAY TYPE

3 - 0.7 in TFT

Polysilicon LCDs

CONTRAST RATIO

500 : 1

WEIGHT

6 lbs / 2.7 kg

DIMENSIONS

12.2 x 3.8 x 10.6 in

310 x 96 x 270 mm

LAMP

180 watts, NSH

LAMPLIFE

2000 hours

DIAGONAL IMAGE SIZE

40 - 300 in

PROJECTION LENS

manual zoom 1:1.2 ratio,

F / 1.75 - 2.1 F=26.7 - 32mm

THROW DISTANCE

4.75 - 37.4 ft

1.45 - 11.29 mm

AUDIO

1 X 2 watt speakers



The BOXLIGHT CP745e projector has an ambient light feature that can automatically detect the lighting in a room and adjust accordingly (brighter or dimmer) which can save lamp life.

Input Panel



Automatic set-up and direct key access for major functions make the CP745e easy to use.

SPECIAL FEATURES:

Auto Keystone & Ceiling Mount

Automatic keystone for a perfectly uniform image.

No fuss with menu system to adjust projector from front, rear or ceiling mount.

HDTV Compatible

Compatible with 1080i, 720p HDTV standards

Multiple Inputs

Connect to multiple computers and one peripheral system at the same time.

INPUTS

2 - 15 pin VGA

1 - Composite

1 - S Video

1 - Component

1 - Mini jack audio

OUTPUTS

1 - RGB

1 - USB mouse

1 - RS 232

POWER SUPPLY

100-240V, 50/60Hz

UL Certified

KEystone

+ / - 30° vertical

VIDEO

NTSC, PAL, SECAM,

1080i, 720p, 480p

DECIBEL RATING

33dB / 30dB eco

FCC CERTIFICATION

Class B

SHIPS WITH:

Remote control

USB mouse cable

Composite AV cable

Power cord

VGA cable

Stereo audio cable - RCA (L/R)

S-Video

Soft carry case

User manual

WARRANTY:

Two year parts and labor (120-day/500 hour lamp guarantee)

BOXLIGHT®
Presenting a Better Way

19302 Powder Hill Place, Suite 101
Poulsbo, WA 98370

www.boxlight.com
Direct - 800.762.5757
International - 360.779.7901
Partners - 866.688.3636