

Christie CP4425 RGB

CHRISTIE CP4425 RGB



Top

Brief Introduction

Beta 2.5

Display Type

Ansi-Lumen

Contrast

Black Level

Offset

Resolution

Video Modes

3D Compatibility

Application

Light Source

Light Life

Operating Costs

Focus

Zoom

Objective

Throw Ratio

Audio

Connections

The CP4425 RGB 3D laser DLP has 26000 Ansi lumens, a contrast of 6000:1 and a UHD (4K+2K) 4096 x 2160 resolution. The manufacturer Christie specifies a service life of 50,000 hours, which would be over 34.2 years with a daily viewing time of 4 hours. A picture width of up to 1292 cm is possible as the projector has 26000 Ansi lumens. The projector can create rooms with residual light with a smaller image width, we recommend a maximum of 861 cm. Furthermore, it is Full HD 1080P and 4K as well as 3D compatible, meaning that all currently available Blu-ray formats can be recognized by the projector.



1,38" Enhanced 4K 3-chip DMD DLP Chip
UHD 19/10 Ti Digital Light Processing Chip

Projector

26000

6000:1 full on/off

4,3333 min. Lumen

Screen

12326 Lux (200 cm Screen width)

6000:1 full on/off

2,055 min. Lumen

UHD (4K+2K) 4096 x 2160
8.847.360 Pixel

Pal, SECAM, NTSC, HDTV 720p, 1080i, 1080p, 4K UHD, 3D, EDTV 480p, 576p
Frame-Packing (Full HD 3D) | Side-by-Side | Top-and-Bottom
Frame Sequential (3D Ready) | 2D-zu-3D Video Converter

Event | Very large screen width and rooms with plenty of light and shaded daylight.

Laser Class 1 – Risk Group 3

50000 h.

0,00 € Laser

Powered


Powered

optional

optional

-

Christie® CineLife+™ Series (Series-2 IMB compatible)
2x HDMI in
2x Display Port
4x 12G SDI
RS232C Din 9 pin in
RJ45 in
Remote UI





Ceiling Mounting Yes, is possible.
Power -
Size WxHxD 944 x 525 x 711 mm (37,2"x20,7"x28") 352,37 L/dm³
Operating Noise 56dB

Weight 130,00 kg / 286,6 lbs.
Keystone -
Illumination -

Frequenz -

Foot-Lamberts 1145 fL / max. 1292 cm screen width
3923 cd/m²

Features ■ Real Full HD 3D
 ■ Full HD 1080P compatible
 ■ Lan network compatible.

Screen Mirroring -

Optional Lenses						
Name	Ratio	Distance	Shift V	Shift H	Zoom	
Zoom Optional Lenses						
4.98-7.69:1 ultra high contrast lens 163-110103-XX	4.98-7.69:1	10-15.4 m				Powered
4.98-7.69:1 high brightness lens 108-280101-XX	4.98-7.69:1	10-15.4 m				Powered
3.89-5.43:1 ultra high contrast lens 163-109101-XX	3.89-5.43:1	7.8-10.9 m				Powered
3.89-5.43:1 high brightness lens 108-279101-XX	4.3-6:1	8.6-12 m				Powered
2.71-3.89:1 ultra high contrast lens 163-108100-XX	2.71-3.89:1	5.4-7.8 m				Powered
2.71-3.89:1 high brightness lens 108-278101-XX	2.71-3.89:1	5.4-7.8 m				Powered
1.95-3.26:1 ultra high contrast lens 163-107109-XX	1.95-3.26:1	3.9-6.5 m				Powered
1.95-3.26:1 high brightness lens 108-338105-XX	1.95-3.26:1	3.9-6.5 m				Powered
1.63-2.71:1 ultra high contrast lens 163-106108-XX	1.63-2.71:1	3.3-5.4 m				Powered
1.63-2.71:1 high brightness lens 108-337104-XX	1.63-2.71:1	3.3-5.4 m				Powered
1.45-2.17:1 ultra high contrast lens 163-105107-XX	1.45-2.17:1	2.9-4.3 m				Powered
1.45-2.17:1 high brightness lens 108-336103-XX	1.45-2.17:1	2.9-4.3 m				Powered
1.31-1.85:1 ultra high contrast lens 163-104106-XX	1.31-1.85:1	2.6-3.7 m				Powered
1.31-1.85:1 high brightness lens 108-335102-XX	1.45-2.05:1	2.9-4.1 m				Powered
1.13-1.72:1 zoom (UHC-P/4K/1.39DLP) 163-145101-XX	1.13-1.72:1	2.3-3.4 m				Powered
1.13-1.66:1 ultra high contrast lens 163-103105-XX	1.13-1.66:1	2.3-3.3 m				Powered
1.13-1.66:1 high brightness lens 108-342100-XX	1.13-1.66:1	2.3-3.3 m				Powered

Status 2022 Current model // Last update of the data: 2025-09-09
Created: 2023-01-17 10:42:55

Data



More Details



HCinema

<https://www.projector-database.com/pro/christiecp4425rgb-en.html>

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.