

CTX UltraVision Projector Series

> PS-6250 LCD Projector >

Display Type

1.3" x 3 Poly-silicon Active Matrix TFT Panels

Resolution

1024 pixels (H) x 768 pixels (V)

Brightness

2500 ANSI Lumens

Contrast Ratio

400:1 (Typical)

Color Palette

16.7M colors

Lamp

200 Watt User Replaceable UHL Lamp

Lamp Life

2000 Hours

Image Size

30" – 300"

Projection Distance

4.4' – 47'

Projection Lens

Power zoom/focus; F#2.0, f=55 - 72mm

Frequency Range

Horizontal: 15.36 – 86KHz

Vertical: 50 – 85Hz

Input Terminal

VGA : 15pin D-sub x2

Video: S-Video, RCA jack, Y, Cb, Cr

Audio: R/L RCA jack, Stereo mini jack x2

Control: PS/2 Mouse

Included Accessories

Deluxe Carrying Case, User's manual, VGA Cable, Power Cord, PC Audio Cable, AV Cable, S -Video Cable, 1 piece of Air Filter, AAA battery for remote, Wireless IR remote control with laser pointer



Multimedia Audio

Built-in Stereo 3D speakers

Built-in amplifier with 3 watt output

Aspect Ratio

4:3 and 16:9

Projection Method

Front, Rear, Ceiling

Compatibility

VGA, SVGA, XGA, SXGA, Mac

NTSC/NTSC4.43/PAL/PAL-M/SECAM

HDTV, 480p, 720p, 1080i

Digital Keystone Correction

± 15 degrees

User Controls

Complete on-screen menu adjustments

Power Consumption

300 Watt in normal use

15 Watt in stand-by mode

Power Supply

AC 100 – 240V / 50 – 60Hz

Operation Temperature

Operating: 50°F-104°F (10°C-34°C)

Storage: -4°F-140°F (-20°C-60°C)

Weight

15 lbs (6.8 Kg)

Dimensions

13.7(W) x 5.5(H) x 10.7(D) inches

Warranty

Two year limited parts and labor, 90 days on lamp

> LCD DISPLAYS > CRT DISPLAYS > PROJECTORS > MULTIMEDIA DISPLAYS >

CTX INTERNATIONAL, INC.

16720 E. Gale Ave.

City of Industry, CA 91745

Website: www.ctxintl.com

Tel: 626.709.1000 Fax: 626.855.7481

© 2002 CTX International Inc. All rights reserved.

Specifications are subject to change without notice.

