ImagePro 8762
Portable DLP Projector

- 2600 Lumens Brightness
- XGA Resolution
- 1600:1 Contrast Ratio
- Only 4.4 lbs.
- Quick Set-Up and Cool Down
- Automatic Keystone Correction
- Automatic Focus
- Automatic Start-Up
- Automatic Shut-Down
- Multi-Level Security Features

8762
DUKANE

ImagePro 8762
Portable DLP projector

The Dukane ImagePro 8762 is an outstanding DLP projector for your classroom or conference room. One of the first automatic projectors sporting a footprint smaller than a sheet of paper.



The 8762 is bright and light. And with it's enhanced security features you can feel confident that your projector is protected.

This quiet, fully Automatic DLP projector cost less than you think and is a great value for your business or classroom.

Key features:

- 2600 Lumens Brightness
- XGA Resolution
- 1600:1 Contrast Ratio
- Only 4.4 lbs.
- Quick Set-Up and Cool Down
- Automatic Keystone Correction
- Automatic Focus
- Automatic Start-Up
- Automatic Shut-Down
- Multi-Level Security Features

8762 Projection Table

Image Size 4:3		Throw Distance		
Diagonal	Width	Min.	Max.	b*
Inches	Inches	Inches	Inches	Inches
30	24	42	51	9
40	32	57	69	12
60	48	86	104	18
80	64	115	139	24
100	80	145	174	30
120	96	174	209	36
150	120	218	261	45
200	160	291	349	60
240	192	350	419	72
300	240	438	524	90

b* = Vertical distance between lens center and screen center

Throw Ratio (distance to width) 1.8 2.2

DUKANE

Dukane Corporation
Audio Visual Products Division
2900 Dukane Drive
St. Charles, Illinois 60174
800-676-2485 toll-free
630-584-5156 fax
avsales@dukcorp.com e-mail
www.dukcorp.com/av

ImagePro is a registered trademark of Dukane Corporation
#11693-B-06.1

Specifications	8762
Image Element	0.7" 12 degree DDR DMD DLP by Texas Instruments, XGA
Brightness	2600 ANSI lumens (2200 lumens in Whisper Mode)
Resolution	1024 x 768 pixels, XGA
Contrast	1600:1
Scanning Frequency	fh 15-100 kHz, fv 50-85 Hz
Lens	Manual zoom, manual/automatic focus (F2.4-2.6), 1.2x zoom
Lens Throw Ratio	1.8-2.2:1 throw distance to image width
Keystone Correction	Automatic +/- 15 deg
Aspect Ratio	4:3, 16:9, selectable
Computer Compatibility	SVGA, VGA, XGA, and SXGA+ Compressed Mac 13" and Mac 16"
Video Compatibility	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, PAL60, SECAM, HDTV 1080i, 720p, 576i/p, 480i/p
Mouse Control	Using optional USB receiver to PC
Image Control	Freeze function
Projection Modes	Front/rear/ceiling
Color Reproduction	24 bit (16.7 million)
Lamp	200W AC
Lamp Life	2000 hours, 2500 in Whisper Mode
Audio	1W x 1
Throw Distance	42" to 524"
Screen Size, diagonal	30" to 300" diagonal
Inputs, Video	(1) RCA, composite video (1) S-video, Min DIN 4-pin
Inputs, Computer	(1) RGB Signal: D-sub, 15 pin
Inputs, Audio	(1) Audio, Stereo mini jack
Outputs, Control	PC control DIN 8 pin
Security	Kensington slot & password protection
Fan Level	37dB, 33dB in whisper mode
Operating Temperature	41 to 104 deg. F (5-40 deg C)
Power	AC 100-120V, AC200-240V 50/60 Hz, 260W Normal, 230W in Whisper Mode
Size (WxHxD)	10.2" x 3.5" x 8.2"
Weight	4.4 lbs.
Carton Size	15.2" x 14" x 18.3"
Shipping Weight	14 lbs.
Accessories Included	Remote control, RGB cable, power cord, operators manual, CDROM, soft carry case
Safety	UL/CSA, FCC Class B
Optional Accessories	Lamp 456-8762 Ceiling mount, universal; RPA-U Remote mouse receiver; IRRCVR

Two (2) year limited warranty on parts and labor in North America, lamp excluded (for other locations, local warranties apply).Includes Dukane's FREE 1 year *Peace-of-Mind Loaner Program*.

2YR