Dukane ImagePro 9126-4K

EAN/UPC:605194006731





The large-screen ImagePro 9126-4K 3D laser DLP has 26000 Ansi lumens, a contrast of 30000:1 and a UHD (4K+2K) 4096 x 2160 resolution. Thanks to the laser, the service life is 20000 hours, which is over 13.7 years with a daily viewing time of 4 hours. As the projector has horizontal and vertical keystone correction, the projector can be set up with plenty of free space in the room, 26000 Ansi lumens ensure that a picture width of 369 cm is also possible. The

projector manages rooms with residual light with a smaller image width, max. 246 cm is

recommended. If the image width is not sufficient, the projector offers integrated edge blending software, which allows several projectors to project a large image together. Furthermore, the projector can play 1080P and 4K as well as 3D without any problems, and thus all currently offered Blu-ray formats can be recognized by the projector. This model is no longer offered by

φ12326 Lux (bei 200 cm Screen)

ด 30000:1 full on/off 9 0,411 min. Lumen

Brief Introduction

Dukane, but is still very popular in our projector database. 3 x 1,38 " DC4K DLP Chip UHD 19/10 Ti Digital Light Processing Chip

Ansi-Lumen Contrast Black Level

Display Type

Offset Resolution

Video Modes

3D Compatibility Application

Light Source Light Life

Operating Costs

Focus

Zoom

Audio

Objective

Throw Ratio

Connections

2 x HDMI in(v2.0 HDCP) 2 x Display Port

HDBaseT Quad 3G-SDI

UHD (4K+2K) 4096 x 2160 8.847.360 Pixel

30000:1 full on/off

0,8667 min. Lumen

Pal, SECAM, NTSC, HDTV 720p, 1080i, 1080p, 4K UHD, 3D, EDTV 480p, 576p

Frame-Packing (Full HD 3D) | Side-by-Side | Top-and-Bottom

Frame Sequential (3D Ready)

Event | Very large screen width and rooms with plenty of light and shaded daylight.

20000 h.

26000

0,00 € Laser

Powered

optional

optional

Powered

19/10 screen width:200 cm Screen:1 Gain

Lux:12326 Lux Room light max.: 2465 Lux Candela pro m²:3923 cd/m² Foot-Lamberts:1145 fL

3D Sync USB in

RS232C Din 9 pin in

RJ45 in

Ceiling Mounting

Yes

Power -

Size WxHxD 697 x 455 x 1180 mm (27,4"x17,9"x46,5") 374,22 L/dm³

Operating Noise 55dB

Weight 169,00 kg / 372,58 lbs.

Keystone Vert.: +/-40° Hori.: +/-40°

Illumination -

Frequenz H-sync: 15-153 kHz V-sync: 24-120 Hz

Foot-Lamberts 1145 fL / max. 369 cm screen width

3923 cd/m²

Real Full HD 3D

Features Full HD 1080P compatible

■ Edge Blending

Lan network compatible.

Optionaler Zubehör

 Objektiv Original
 100014026 / L2K-10F1
 EOL €

 Objektiv Original
 100014016 / L2K-43ZM1
 EOL €

 Objektiv Original
 100014017 / L2K-55ZM1
 EOL €

Optional Lenses

Name	Ratio	Distance	Shift V	Shift H	Zoom
Zoom Optional Lenses					
L4K20ZM	2-3.4:1	4-6.8 m	+/-0.17%	+/-0.50%	Powered
L4K-15ZM	1.5-2.1:1	3-4.2 m	+/-0.17%	+/-0.50%	Powered
L4K-11ZM	1.1-1.7:1	2.2-3.4 m	+/-0.17%	+/-0.5%	Powered
L2K30ZM	2.7-3.9:1	5.4-7.8 m	0.27-0.19%	+/-0.08%	Powered
L2K-55ZM1	4.8-7.4:1	9.6-14.8 m	0.31-0.19%	+/-0.1%	Powered
L2K-43ZM1	3.7-5.3:1	7.4-10.6 m	0.27-0.19%	+/-0.08%	Powered
Fix Optional Lenses					
L2K-10F1	0.9:1	1.8 m	0.27-0.19%	+/-0.08%	No Zoom

Status 2018 Discontinued (EOL) // Last update of the data: 2024-11-15

Created: 2018-04-25 20:16:10

Data



More Details



HCinema

https://www.projector-database.com/pro/dukaneimagepro91264k-en.html

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.