

MULTIMEDIA PROJECTOR

EMP-820 PROJECTOR



XGA HIGH-BRIGHT PROJECTOR FOR DESKTOP PRESENTATIONS OR INSTALLATIONS

- 2500 ANSI Lumens
- DVD, DTV, HDTV compatible
- Horizontal Keystone Correction
- sRGB mode
- Analogue and digital compatibility
- Multiple source input

EPSON®



SYDNEY
70 Gibbes Street
Chatswood NSW 2067
Tel: (02) 9903 9000
Fax: (02) 9903 9177

MELBOURNE
Level 1
6 Riverside Quay
Southbank VIC 3006
Tel: (03) 9685 6555
Fax: (03) 9686 1016

BRISBANE
Level 3, Waterfront Place
1 Eagle Street
Brisbane QLD 4000
Tel: (07) 3360 0219
Fax: (07) 3360 0289

PERTH
Suite 20, Level 3
1060 Hay Street
West Perth WA 6005
Tel: (08) 9480 0418
Fax: (08) 9480 0443

ADELAIDE
Level 1, Carrington House
61-63 Carrington Street
Adelaide SA 5000
Tel: (08) 8237 0518
Fax: (08) 8237 0519

AUCKLAND
245 Hobson Street
Auckland NZ
Tel: (09) 366 6855
Fax: (09) 366 6865

WELLINGTON
Level 6, City Tower
95 Custom House Quay
Wellington NZ
Tel: (04) 473 3494
Fax: (04) 473 4631

ABN 91 002 625 783
05 /02

Visit our website:

www.epson.com.au
www.epson.co.nz

MULTIMEDIA PROJECTOR

EPSON EMP-820 Projector



Specifications

PROJECTION SYSTEM		RGB Liquid Crystal Shutter Projection System
PROJECTION METHOD		Front / Rear / Ceiling Mount
SPECIFICATION OF MAIN PARTS		
LCD	Size	0.9inches with MLA (x3)
	Driving method	Poly-Silicon TFT active matrix
	Pixel number	786,432 (1024 x 768) x 3
	Native resolution	XGA
	Aspect ratio	4:3
PROJECTION	Pixel arrangement	Stripe
	Type	Manual: zoom / focus
	f-number	1.74 to 2.06
	f-number	28.3 to 37.98mm
	Zoom ratio	1:1.35
LAMP	Lens cover	attached
	Type	200 W UHE
OPTICAL SYSTEM		Dichroic Mirror Separation & Prism combine method
SCREEN SIZE (PROJECTED DISTANCE)		30 to 300inch (0.87 to 12.48m)
KEYSTONE CORRECTION RATIO		10:0
BRIGHTNESS		2500 ANSI lumens
CONTRAST		400:1
BRIGHTNESS UNIFORMITY		85%
COLOUR REPRODUCTIVITY		Full colour (16.7 million colours)
SOUND OUTPUT		5W
EFFECTIVE SCANNING FREQUENCY RANGE		
PIXEL CLOCK		14MHz to 230MHz
HORIZONTAL		(15 - 107) KHz
VERTICAL		(43 - 120) Hz
ADJUSTMENT FUNCTION		
PROJECTOR / REMOTE CONTROL		Keystone (Vertical and Horizontal) / Brightness / Contrast / Tint / Sound / Input signal etc.
KEYSTONE CORRECTION		Vertical -30 to +30 degrees Horizontal -10 to +10 degrees
TILT ANGLE		0 to 12 degrees

ANALOGUE RGB I/O		
DISPLAY PERFORMANCE	Native	1024 x 768 dots
	Resize	1600 x 1200 / 1280 x 1024 / 800 x 600 / 640 x 480 dots
INPUT SIGNAL	Signal type	Separate signal
	Video signal	Analogue (0.7Vp-p, 75 Ω / Mac 0.714Vp-p, 75 Ω)
	Sync. signal	Separate (positive & negative, bi-polarity 1-5Vp-p) / Composite (positive & negative, bi-polarity 1-5Vp-p) / Sync-on-green (negative 0.3Vp-p)
INPUT TERMINAL	Audio signal	500m Vrms / 47 KΩ
	Video	DVI Type I x 1 (DDC 2B compatible, Analogue / Digital auto detect)
	Audio	Mini D-sub 15 pin x 1 Stereo mini jack RCA x 2
OUTPUT SIGNAL	Video signal	Analogue (0.7Vp-p, 75 Ω / Mac 0.714Vp-p, 75 Ω)
	Sync. signal	Separate (positive & negative, bi-polarity 1-5Vp-p) / Composite (positive & negative, bi-polarity 1-5Vp-p) / Sync. on green (negative 0.3Vp-p)
OUTPUT TERMINAL	Video	Mini D-sub 15pin x 1
DIGITAL RGB INPUT		
DISPLAY PERFORMANCE	Native	1024 x 768 dots
	Resize	1280 x 1024 / 800 x 600 / 640 x 480 dots
INPUT SIGNAL	Video signal	Digital
	Audio signal	500m Vrms / 47 KΩ
INPUT TERMINAL	Video	DVI Type I x 1 (DDC 2B compatible, Analogue/Digital auto detect)
	Audio	Stereo mini jack

VIDEO I/O		
DISPLAY PERFORMANCE		NTSC: 550 lines PAL: 550 lines (Depend on observation of the multi burst pattern)
		NTSC / NTSC4.43 / PAL / M-PAL / N-PAL / PAL60 / SECAM
INPUT SIGNAL	Video standard	Composite Video (1.0Vp-p/ Sync.negative, 75 ohm) / S- Video (Luminous 0.714Vp-p, Chrominous 0.286Vp-p, 75 ohm) / Component Video (Analogue Y level 0.7V 75 ohm/ Cr Cb level +/-0.35V 75 ohm/ sync.negative 0.3V or 3-state +/-0.3V on Y) / Video-RGB (0.7Vp-p, 75 ohm/ Mac 0.714Vp-p, 75 ohm)
	Audio signal	500m Vrms / 47 KΩ
INPUT TERMINAL	Video	Composite Video: RCA x 1 / S-Video: Mini DIN / Component Video: Mini D-sub 15pin / Video-RGB: Mini D-sub 15pin
	Audio	RCA x2 (for Composite Video/S-Video / Component Video) Stereo mini jack (for Video-RGB)

CONTROL I/O		
MOUSE I/O / USB I/O	I/O terminal	Mini DIN 9pin x1 (for PS/2 mouse) / USB connector series A x1 (for HUB) USB connector series B x1 (for mouse, K/B, audio, control)
SERIAL I/O	I/O terminal	Mini D-sub 9pin x1
	I/O serial	RS-232C
INPUT TERMINAL	Remote Control	Stereo mini jack x1
OPERATING TEMPERATURE		5°C to 35°C (41°F to 95°F)
POWER SUPPLY VOLTAGE		100 - 120V / 200 - 240V ±10%, 50/60Hz AC
DIMENSION		
EXCLUDE PROJECTION LENS & FEET		348(W) x 104(H) x 274(D)mm
MAXIMUM DIMENSION		349(W) x 114(H) x 276(D)mm
WEIGHT		Approx. 9.3lbs / 4.2Kg
FAN NOISE		38dB
ACCESSORIES		
		Power cable (3m), Computer cable (1.8m), Mini D-sub 15pin (Male) - Mini D-sub 15pin (Male), Video/Audio cable (RCA x3 (White, Red, Yellow), Mouse cable (PS/2 Mouse cable) (USB Mouse cable), Remote Control, Battery (AA x 2), User's manual

WARRANTY		
STANDARD WARRANTY		2 years

* Specifications are subject to change without notice due to technological improvements.



As an International ENERGY STAR Partner, EPSON has determined that this product meets the International ENERGY STAR guidelines for energy efficiency. EPSON is the registered trademark of SEIKO EPSON Corporation. EPSON STYLUS, PerfectPicture, MicroPiezo, AcuPhoto Halftoning, QuickDry are the trademarks of SEIKO EPSON Corporation. All other names and company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. EPSON disclaims any and all rights in those marks. All print samples shown herein are simulations. Specifications are subject to change without notice.

EPSON®