

VS340 XGA 3LCD Projector

Advanced
presentations
XGA resolution



The affordable portable projector ideal for advanced presentations.

Far more accurate color with Epson® — 3LCD, 3-chip technology for 3x Higher Color Brightness¹ and up to 3x Wider Color Gamut² than competitive DLP projectors

Look for two numbers:

2800 lumens³ Color Brightness for more accurate, vivid color
2800 lumens³ White Brightness for well-lit rooms

XGA resolution (1024 x 768) — 1.5x more resolution than SVGA for projecting advanced presentations with text-heavy charts and spreadsheets

Fast, easy setup, only from Epson — get up and running in no time with easy image adjustments and convenient control

Compatible with the latest laptops and media players — supports HDMI®, the standard in connectivity, for digital video and audio with just one cable



Specifications

Projection System 3LCD, 3-chip technology
Projection Method Front/rear/ceiling mount
Driving Method Poly-silicon TFT Active Matrix
Pixel Number 786,432 dots (1024 x 768) x 3
Color Brightness³ Color Light Output: 2800 lumens
White Brightness³ White Light Output: 2800 lumens
Aspect Ratio 4:3
Native Resolution 1024 x 768 (XGA)
Resize Support 800 x 600 (SVGA), 1152 x 864 (SXGA), 1280 x 800 (WXGA), 1280 x 960 (SXGA2), 1280 x 1024 (SXGA3), 1440 x 900 (WXGA+), 1400 x 1050 (SXGA+)
Lamp Type 200 W UHE
Lamp Life⁵ Up to 5000 hours (Normal Mode) and up to 10,000 hours (ECO Mode)
Throw Ratio Range 1.48 (Zoom:Wide), 1.77 (Zoom:Tele)
Size (projected distance) 30" – 300" (0.9 – 9.0 m)
Keystone Correction Auto Vertical: ± 30 degrees
Keystone Correction Manual Horizontal: ± 30 degrees (Easy-Slide Horizontal Image Correction)
USB Plug 'n Play Projects audio and video, PC and Mac® compatible
Contrast Ratio Up to 15,000:1
Color Reproduction Up to 1.07 billion colors

Projection Lens

Type Manual focus
F-number 1.58 – 1.72
Focal Length 16.9 mm – 20.28 mm
Zoom Ratio Optical zoom 1.0 – 1.2

Other

Display Performance NTSC: 480 lines PAL: 576 lines (Depends on observation of the multi-burst pattern)
Input Signal NTSC/NTSC4.43/PAL/M-PAL/N-PAL/PAL60/SECAM
Speaker 1W (mono)
Operating Temperature 41 ° to 95 °F (5 ° to 35 °C)
Power Supply Voltage 100 – 240 V ±10%, 50/60 Hz
Power Consumption
 291 W (Normal Mode)
 214 W (ECO Mode)
Fan Noise
 37 dB (Normal Mode)
 29 dB (ECO Mode)
Security Kensington®-style lock provision, password protect function

Interfaces

HDMI x 1
 Computer/component video: D-sub 15 pin x 1
 S-video: Mini DIN x 1
 Composite video: RCA (Yellow) x 1
 Audio in: RCA x 1 (White/Red)
 USB connector Type A x 1: PC-free USB and other
 USB connector Type B x 1: USB Plug 'n Play



Dimensions (W x D x H)

Including Feet: 11.7" x 9.2" x 3.2"
Excluding Feet: 11.7" x 9.2" x 3.0"
Weight: 5.29 lb

Remote Control

Features Source search selection, power, volume, e-zoom, A/V Mute, freeze, menu, page up and down, help, auto, mouse functions

Operating Angle

Right/left: ± 30 degrees
 Upper/lower: ± 15 degrees

Operating Distance 19.7 ft (6 m)

Eco Features

RoHS compliant
 Recyclable product⁶
 Epson America, Inc. is a SmartWaySM Transport Partner⁷

Support

Epson ConnectionSM

Pre-sales support U.S. and Canada 800-463-7766
 Internet website www.epson.com

Service Programs One-year projector limited warranty, Epson Road Service program, PrivateLine[®] dedicated toll-free support and 90-day limited lamp warranty

What's in the Box

VS340 Projector, Power Cable, Computer Cable (VGA), Projector Remote Control, Batteries, User Manual CD, Quick Setup Sheet

Ordering Information

VS340 Projector	V11H717220
Genuine Epson Lamp (ELPLP88)	V13H010L88
Replacement Air Filter (ELPAF32)	V13H134A32
Soft Carrying Case (ELPKS63)	V12H001K63
Universal Projector Ceiling Mount	ELPMBPJF
Duet TM Screen	ELPSC80F
ES3000 Screen (ELPSC26H)	V12H002S3Y
ES1000 Screen	V12H002S4Y
Kensington Security Lock	ELPSLO1

¹ Color brightness (color light output) measured in accordance with IDMS 15.4. Color brightness will vary depending on usage conditions. Leading Epson 3LCD business and education projectors compared to leading 1-chip DLP projectors, based on NPDP data for June 2013 through May 2014 and PMA Research data for Q1 through Q3 2013. ² Gamut volume of leading Epson business and education projectors compared to leading 1-chip DLP projectors, based on NPDP data for June 2013 through May 2014. Volume is measured in 3D in the CIE L*a*b* coordinate space. ³ Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. ⁴ Based on TFCinfo: U.S. Projector Brand Customer Perception and Preference Study, Multimedia Projectors 2015. ⁵ Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time. ⁶ For convenient and reasonable recycling options, visit www.epson.com/recycle. ⁷ SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

Better Products for a Better Future[™]
eco.epson.com



Epson America, Inc.
 3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada Limited
 185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com
www.epson.ca

Specifications and terms are subject to change without notice. EPSON is a registered trademark, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. PrivateLine is a registered trademark, Duet is a trademark and Epson Connection is a service mark of Epson America, Inc. Mac is a trademark of Apple Inc., registered in the U.S. and other countries. SmartWay is a service mark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks.
 Copyright 2015 Epson America, Inc. Com-SS-Oct-13 CPD-43118 6/15