





Brief Introduction Beta 2.5

Resolution

Application

A brief introduction to the Everest SX 880. The LCD projector has an XGA 1024 x 768 resolution and 3500 Ansi lumens. The projector can illuminate images up to 515 cm wide thanks to its 3500 Ansi lumens. The projector can create rooms with residual light with a smaller image width, we recommend a maximum of 343 cm. On the market since 2009, the model is no longer offered by the manufacturer Everest. 3 x LCD TFT Panel

Display Type

XGA 4/3 Liquid Crystal Display

Ansi-Lumen 3500 rojector Contrast Black Level

Offset

XGA 1024 x 768 786.432 Pixel

UXGA 1600 x 1200 compressed Video Modes

PAL, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p

Standard-Portabel | External training and company presentations, as well as product

presentations.

Medium screen width or rooms with a little more ambient light, max. 200 lumens.

Light Source 200 / 180W im Eco Mode Lamp Light Life 2000 h. 3000 h. in Eco Mode

Operating Costs

Manual Focus

Zoom **Manual 11.23**

Objective

Throw Ratio 1,651-18,541:1

1 x 8W Audio

DVI-I in

D-sub 15 pin in und out S-Video in

Cinch Video in Cinch Stereo in RS232C Din 9 pin in

USB Typ B

Ceiling Mounting Yes

Connections

Power 310W

Size WxHxD 325 x 97 x 260 mm (12,8"x3,8"x10,2") 8,2 L/dm3

Operating Noise 33 dB in Eco Mode

Weight 3,40 kg / 7,5 lbs.


Vert.: +/-30° automatisch Keystone


Illumination

H-sync: 31-92 kHz Frequenz V-sync: 48-120 Hz

Foot-Lamberts 108 fL / max. 515 cm screen width

370 cd/m²





Features

Eco Mode

■ Automatic and manual vertical keystone correction

■ Remote control with laser pointer

2009 Discontinued (EOL) // Last update of the data: 2023-09-01

Status Data

More Details





Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.