

Knoll Systems HDUS110



KNOLL SYSTEMS HDUS110



1 x 0,65" DLP Chip
4/3 Ti Digital Light Processing Chip

Display Type		
Ansi-Lumen	Projector 3500	Screen 1167 Lux (bei 200 cm Screen)
Contrast	10000:1 full on/off	10000:1 full on/off
Black Level	0,3500 min. Lumen	0,117 min. Lumen
Offset	-	
Resolution	-	
Video Modes	Pal, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p	
3D Compatibility	Frame Sequential (3D Ready)	
Application	Standard-Portabel External training and company presentations, as well as product presentations. Medium screen width or rooms with a little more ambient light, max. 200 lumens.	
Light Source	-	
Light Life	Articel Nr.: LMP23468 3000 h. 7000 h. in Eco Mode	
Operating Costs	-	
Focus	Manual	
Zoom	Manual	
Objective	-	
Throw Ratio	-	
Audio	20W	
Connections	HDMI in D-sub 15pin in und out S-Video in Mini Jack Audio in und out RS232C Din 9 pin in	
Ceiling Mounting	Yes	
Power	280 / 230W in Eco Mode	
Size WxHxD	288 x 123 x 375 mm (11,3"x4,8"x14,8") 13,28 L/dm³	
Operating Noise	37 / 32 dB in Eco Mode	



Weight	5,00 kg / 11,02 lbs.
Keystone	-
Illumination	-
Frequenz	-
Foot-Lamberts	108 fL / max. 515 cm screen width 370 cd/m²
Features	■ Eco Mode ■ 6 -segment, 4-speed Farnrad.
Status Data	2015 Discontinued (EOL) // Last update of the data: 2023-08-04



[More Details](#)

HCinema

<https://www.projector-database.com/pro/knollHDUS110-en.html>

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.