

Photon Life PH32ST

Photon Life PH32ST Short throw Home Projector



- **Photon Life - Perfect for any room in the house**
- **Bright 3100 lumens for lights on viewing - Full HD 1080p 4LED projector**
- **Short throw lens for gaming - 100" image from just over a metre away**
- **Optoma Smart Control App - Providing the ultimate flexibility, this projector's short throw lens is perfect for smaller spaces and combined with Optoma's new SmartApp, allows for quick adjustments to your setup all from your mobile device**



The PH32ST is one of Optoma's most compact and hassle-free Full HD projectors to date. Designed for maintenance-free continuous operation, this 3100-lumen projector delivers powerful image performance and provides an easy setup in any space around the home, with a short throw lens and extensive connectivity options in a sleek, compact form factor.

Use Optoma's latest Smart Control App to make quick adjustments to your setup and take advantage of low latency gaming mode for lighting quick response times.

Specifications

EAN: 5055387600782, Colour: Black



Display/image	
Display technology	DLP®
Resolution	1080p Full HD (1920x1080)
Brightness	3,100 lumens
Contrast ratio	500,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction - horizontal	+/-30°
Keystone correction - vertical	+/-30°
Displayable colours (millions)	1073.4
Horizontal scan rate	15 ~ 135Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	85%
Screen size	0.76m ~ 7.62m (30" ~ 300") diagonal
Lamp info	
Light source type	4 LED
LASER life	30,000 hours
Optical	
Throw ratio	0.69:1 ~ 0.83:1
Projection distance (m)	0.458m - 5.512m
Zoom	1.2
Zoom type	Manual
Focal length (mm)	10.2 ~ 12.24
Native offset	102%
Connectivity	
Connections	Inputs 2 x HDMI 2.0, 1 x VGA, 1 x Audio 3.5mm Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A Control 1 x RS232, 1 x RJ45
General	
Noise level (min)	29dB
Noise level (max)	35dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 10000ft.
Speaker count	1
Watts per speaker	10W
In the box	AC power cord Remote control 2x AAA Batteries Basic user manual
Power	
Power supply	AC 100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	<0.5W
Power consumption (min)	124W
Power consumption (max)	226W
Weight and dimensions	
Dimensions (W x D x H) mm	307 x 228 x 125
Gross weight	5 kg
Net weight	3.2 kg