₹ □ ×

projectiondesign FL32 WUXGA





Brief Introduction Beta 2.5

and a WUXGA 1920 x 1200 resolution. The manufacturer specifies an LED service life of 100,000 hours, which is over 68.5 years if enjoyed for four hours a day. With the lens shift function, the projector can be positioned very freely. The projector can illuminate a picture width of up to 278 cm thanks to its 750 Ansi lumens. In room lighting, however, the picture width should ideally be less than 185 cm. The projector can also display 1080P without any problems. On the market since 2009, the model is no longer offered by the manufacturer projectiondesign, but is still very popular in our projector database. 1 x 0,95" DLP Chip

The FL32 WUXGA LED BrilliantColor DLP has 750 Ansi lumens, a contrast of 2000:1 - 7500:1

Display Type

WUXGA 16/9 Ti Digital Light Processing Chip 750

Ansi-Lumen Contrast Black Level Lens shift

2000:1 - 7500:1 full on/off 0,3750 min. Lumen Vert.: +/-58,5%

Resolution

WUXGA 1920 x 1200

2.304.000 Pixel

Video Modes

Application

PAL, SECAM, NTSC, HDTV 720p, 1080i, 1080p EDTV 480p, 576p

Stationary | Permanent installation in the training room and meeting room as well as the

conference room.

Small screen width, rooms with very little ambient light below 100 lumens.

Light Source Light Life

LED 100000 h.

Operating Costs

0,00 € LED

Focus

Powered

Zoom

Powered

Objective

optional

Throw Ratio

optional

Audio

No

Connections

HDMI 1.3 in DVI-D in D-sun 15 pin in

5 x BNC RGBHV in


YUV in

Cinch Video in

RJ45 in

2 x RSereC Din 9 pin in

USB in



2 x 12V Trigger out
Ceiling Mounting
Yes

Power 350W

Size WxHxD 376 x 223 x 510 mm (14,8"x8,8"x20,1") 42,76 L/dm³

Operating Noise -

Weight 12,60 kg / 27,78 lbs.

Keystone -Illumination -

Features

Optional

H-sync: 15-150 kHz
Frequenz
V-sync: 48-190 Hz
Range max.: 205 MHz

Foot-Lamberts 31 fL / max. 278 cm screen width

106 cd/m²

Full HD 1080P compatible

Lens shift FunktionKensington Slot

Gamma correction
Digital image shift

■ 24/7 continuous operation capable

■ BrilliantColor™

■ Remote control with laser pointer und mouse control

■ Lan network compatible.

Object lens original R9801209 / EN14
Object lens original R9801214 / EN11
Object lens original R9801218 / EN12
Object lens original R9801225 / EN15
Object lens original R9801228 / EN13
Object lens original R9801249 / EN16
Order here: https://www.hcinema.de/lampen/shop-en.php?id=hc1570

Optional Lenses

Name	Ratio	Distance	Shift V	Shift H	Zoom
		Zoom Optional	Lenses		
EN16	3.8-6.5:1	7.6-13 m	+/-58.5%	+/-42%	Powered
EN14	2.37-3.79:1	4.7-7.6 m	+/-58.5%	+/-42%	Powered
EN13	1.24-1.6:1	2.5-3.2 m	+/-58.5%	+/-42%	Powered
EN11	1.6-2.32:1	3.2-4.6 m	+/-58.5%	+/-42%	Powered
		Fix Optional L	enses		
EN15	1.16:1	2.3 m	+/-58.5%	+/-42%	No Zoom
EN12	0.79:1	1.6 m	0.0% Fix		No Zoom
Ctatus	2000 Discontinued (EQL) //Lest undete of the date; 2022 09 04				

Status 2009 Discontinued (EOL) // Last update of the data: 2023-08-04

Data

More Details





https://www.projector-database.com/pro/projectiondesignfl32wuxga-en.html

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.

