ProLux WallZapper 1000S



Brief Introduction

Beta 2.5

Offset

Resolution

With the WallZapper 1000S, manufacturer ProLux offers a stationary LCD projector with SVGA 800 x 600 resolution and a contrast of 150:1. The projector can illuminate images up to 238 cm wide thanks to its 750 Ansi lumens. In room light, however, the image width should ideally be less than 159 cm. The model is no longer available from ProLux.

1 x 6,4 LCD TFT Panel

Display Type

SV

SVGA 4/3 Liquid Crystal Display

Ansi-Lumen Contrast Black Level

ਰ ਰ 150:1 full on/off ਉ 5,0000 min. Lumen ω243 Lux (bei 203 cm Screen)
 150:1 full on/off
 1.653 min. Lumen

SVGA 800 x 600 480.000 Pixel

480.000 Pixel XGA 1024 x 768 compressed

Video Modes

NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, HDTV

Stationary | Permanent installation in the training room and meeting room as well as the

conference room.

Metalldampf Lamp

Small screen width, rooms with very little ambient light below 100 lumens.

Light Source

Application

Light Life

2000 h.

Operating Costs

Manual

Zoom

Focus

Audio

No Zoom

Objective

Throw Ratio

2 x 2-W Stereo

D-sub 15pin in und out 2 x Cinch Video in 2 x S-Video in

Connections 2 x S-Video in 2 x Cinch Stereo in

RS232C

Ceiling Mounting Power

Yes 725W

Size WxHxD
Operating Noise

-

Weight Keystone Illumination

> H-sync: 15,0-50,0 kHz V-sync: 56-75 Hz

Foot-Lamberts


23 fL / max. 238 cm screen width

79 cd/m²

Features

Frequenz

Status Data - Discontinued (EOL) // Last update of the data: 2023-08-04



More Details



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.