proxima
InFocus Professional Series

DP6500x

Simply designed
to be shared.

KEY BENEFITS

EASY TO SUPPORT
- New projector design with standardized keypads, menus and interchangeable remotes. Easy to use, easy to share, easy to support

COLOR-CODED CONNECTIONS
- Color-coded cables and velcro straps plug into matching color-coded ports

BRIGHT, CAPTIVATING IMAGES
- 2500 ANSI lumens fill the screen producing bright, captivating images

WHISPER QUIET
- 35dB insure the only thing heard is your message

PROJECTORNET™
- Manage the DP6500x over your corporate network

FLEXIBLE IMAGE PLACEMENT
- The zoom lens allows a change in image size of up to 40% so images fit the screen perfectly from wherever the projector is located

WHAT'S INCLUDED

- **Exclusive InFocus Organizer molded carry case**
- **Conductor™ Plus full-featured remote with laser pointer**
- **Color coded cable straps**
- **M1-D/A analog computer cable with USB**
- **3.5mm computer audio cable**
- **RCA audio/video cable**
- **Power cord**
- **User manual, quick start card and CD**

ORDERING INFORMATION

Optional Accessories

CA-ATA-013	ATA Shipping Case
CASE-801	Deluxe Travel Case
SP-DVI-CARD	Digital/Analog Interface Card
SP-DVI-D	Digital Computer Cable
HW-PRESENTER	Presenter™ remote with laser
HW-RF-POCKTPNT	Mind Path™ RF remote
SP-CEIL-005	Projector Mount
SP-LTMT-PLT	False Ceiling Plate
SP-LTMT-EXTP	Mounting Extension Arm
SP-LOCK	PC Guardian Projector Cable Lock
A650	50" Portable Projection Screen
HW-DLXSCRN	60" Deluxe Insta-Theatre Screen
HW-WALLSCR84	84" Pull-Down Screen
SP-LAMP-006	Replacement Lamp
SP-VGAEXT50-D	50' VGA Extension Bundle
HW-INTEGRATOR	Integrator™ systems remote with laser

TECHNICAL SPECIFICATIONS

Native Resolution	· XGA 1024 x 768
Display Technology	· DLP™ by Texas Instruments 0.7" XGA DMD DDR
Input Sources	· Computer 1 (M1-D/A with 3.5mm audio), computer 2 (VESA with 3.5mm audio), Video 1 (S-Video), Video 2 (Composite RCA), Video 3 (Component RCA), stereo audio (RCA), RS-232 (DB9), NIC (RJ45)
Output Sources	· Stereo audio (RCA), monitor out (VESA)
Computer Compatibility	· SXGA, XGA, SVGA, VGA, Macintosh® , 1080i/720p HDTV
Video Compatibility	· Full NTSC, PAL, SECAM, EDTV (480p, 576p), HDTV (720p, 1080i)
Brightness Standard Mode	· 2500 ANSI lumens
Brightness Uniformity	· +30/-40
Contrast Ratio	· 800:1
Number of Colors	· 16.7 million colors
H-Synch Range	· 50 – 117 kHz
V-Synch Range	· 50 – 85 Hz
Dot Clock	· 135 MHz
Vertical Image Offset	· Fixed. +115% image offset
Digital Keystone Correction	· +/- 20 degrees
Projection Lens	· Manual zoom and focus lens
Zoom Ratio	· 1.4:1
Throw Ratio	· 0.48 – 0.67:1 (Diagonal Image/Distance) · 1.88 – 2.63:1 (Horizontal Image/Distance)
Minimum Projection Distance	· 5' (1.5m)
Maximum Projection Distance	· 32.8' (10.0m)
Aspect Ratio	· 4:3
Image size (diagonal)	· 2.4' to greater than 22' (0.7m to greater than 6.7m)
Projection Methods	· Front, rear and ceiling
Audio	· 2 x 2-Watt stereo audio
Projector Control	· Menu, Keypad, ProjectorManager™, RS-232, NIC (RJ45)
Mouse Control	· USB
Lamp	· 250 W UHP/2000 hours
Dimensions (standard)	· 4.3" (H) x 13.8" (W) x 12.8" (L) 110mm (H) x 351mm (W) x 325mm (L)
Weight (standard)	· 9.35 lbs/4.24 kg
Power Consumption	· 350 Watts
Power Supply	· 100V– 240V at 50– 60 Hz
Operating Temperature	· 10 ° to 35 °C at sea level (0 to 10,000'); 50° to 95° F
Menu Languages	· English, Spanish, French, German, Japanese, Korean, Portuguese, Italian, Norwegian, Russian, Simplified Chinese,Traditional Chinese
Audible Noise	· 35dB
Approvals	· UL, CSA, TUV, C Tick, NOM, MIC, GOST, IRAM, CCC, S-JQA,FCC A, EN55022, ICES-003
Lamp Warranty	· 90 days or 500 hours, whichever comes first
Warranty	· 2 years parts and labor

PROJECTION DISTANCES/IMAGE SIZES*

Distance to Screen		Minimum Diagonal Image Size Throw Ratio: 0.48		Maximum Diagonal Image Size Throw Ratio: 0.67		Minimum Horizontal Image Size Throw Ratio: 2.63		Maximum Horizontal Image Size Throw Ratio: 1.88	
5.0'	1.5m	2.4'	0.7m	3.4'	1.0m	1.9'	0.6m	2.7'	0.8m
10.0'	3.0m	4.8'	1.5m	6.7'	2.0m	3.8'	1.1m	5.3'	1.6m
15.0'	4.6m	7.2'	2.2m	10.1'	3.1m	5.7'	1.7m	8.0'	2.4m
20.0'	6.1m	9.6'	2.9m	13.4'	4.1m	7.6'	2.3m	10.6'	3.2m
30.0'	9.1m	14.4'	4.4m	20.1'	6.1m	11.4'	3.5m	15.9'	4.8m
32.8'	10.0m	15.7'	4.8m	22.0'	6.7m	12.5'	3.8m	17.4'	5.3m

* Metric conversions are approximate.

Alternative View
Multimedia Projection Technology

800.555.4566 • www.AlternativeView.com
2501 Washington Ave. • Midland, MI 48642