

proxima®

Own your audience.



ULTRALIGHT DX3

the brightest of the lightest

THE DLP™ DIFFERENCE

displays photo-realistic color and smooth video

DAZZLING DETAIL

XGA resolution provides the image detail and compatibility you need

HOT MOUSE CONNECTION

USB port lets you hook up instantly during your presentation

BRIGHTEST IN CLASS

1100 ANSI lumens in a five-pound package

FREE REPLACEMENT

two years of free ProXchange service for extra security

ZOOM IN

position the DX3 anywhere and zoom in or out



PROXIMA ULTRALIGHT® DX3 FEATURES

The smallest way to make the biggest impact is with Proxima's ultra-bright, ultra-sleek UltraLight DX3. Never before has Proxima packed this much performance into something so compact and lightweight. You get the high-detailed clarity that comes from XGA resolution, along with best-in-class brightness, for the most impressive images you'll see from a slim, five-pound projector.

- at just five pounds, it offers the utmost in portability without sacrificing important features
- the brightest projector in its class at 1100 ANSI lumens, it's ideal for presenting in brightly lit rooms
- zoom lens offers flexibility in set up, letting you position the projector where you want it and adjust the image size accordingly
- XGA (1024 x 768) resolution lets you display your most detailed images with clarity, and provides compatibility with a wide range of computers
- Digital Light Processing™ technology from Texas Instruments produces photo-realistic images and film-like video
- features DVI (Digital Visual Interface) for a "pure" digital connection to PCs and laptops
- USB port offers hot mouse connection anytime during your presentation
- includes easy-to-use remote control with laser pointer and soft carrying case
- comes with 90-day lamp warranty and two years of free ProXchange™ service for overnight projector replacement in the unlikely event your DX3 is in need of repair
- the premium solution for mobile executives and anyone requiring the best image quality from the smallest projector

WHAT'S INCLUDED

MODEL DX3 INCLUDES:

- Wireless remote control with mouse control and laser pointer
- U.S. and European power cords
- Product documentation, registration card
- VGA cable, audio cable (mini-plug), PC serial, PS/2 and Mac control cables, AV cable, and S-video cable
- Lens cap


[**Presentation solutions**]

DX3 TECHNICAL SPECIFICATIONS

Native Resolution	• XGA (1024 x 768)
Resolution Supported	• VGA (640 x 480), SVGA (800 x 600), XGA (1024 x 768), SXGA (1280 x 1024)
Brightness	• 1100 ANSI lumens
Brightness Uniformity	• > 80%
Contrast Ratio	• 600:1
Computer Compatibility	• IBM PC or compatibles • Apple Macintosh
Video Compatibility	• PAL, PAL-M, PAL-N, SECAM, NTSC 3.58, NTSC 4.43
Display Technology	• Single chip DLP
Number of Colors	• 16.7 million colors
Input Sources	• 1 digital computer (DVI), 1 analog computer, 1 S-video, 1 composite video, 1 audio, 1 USB mouse
H-Sync Range	• 15 - 100 kHz
V-Synch Range	• 43.5 - 130 Hz
Bandwidth	• 160 MHz analog • 112 MHz digital
Keystone Correction (digital)	• $\pm 11^\circ$ - 13.5° adjustable, 110% offset
Projection Lens	• focal length 30 mm to 37.5 mm F/2.6
Projection Distance	• 1.1 m to 10 m (3.6'-32.8')
Zoom	• 1.25:1 manual zoom
Aspect Ratio	• 4:3
Image Size (diagonal)	• 2.1 ft. to 23.4 ft. (.6 m to 7.1 m)
Throw Ratio	• 1.72 - 2.15:1
Audio	• 2 x 1 watt stereo
Remote Control	• Full function remote with laser pointer and mouse control
Lamp (Life)	• 120-watt UHP (2,000 hours)
Dimensions	• 9.6 in. W x 7.7 in. L x 2.7 in. H • 24.5 cm W x 19.5 cm L x 6.8 cm H
Weight	• 5 lbs. (2.3 kg)
Power Consumption	• < 180 watts
Power Requirements	• 90V - 264V AC, 47/63 Hz
Operating Temperature	• 59° to 95° F (15° to 35° C)
On-Screen Menu Languages	• English, French, Spanish, Portuguese, German, Italian, Chinese, Korean, Japanese, Norwegian
Audible Noise	• < 35 dB
Approvals	• CE, UL, cUL, FCC Class A
Warranty	• two years on parts and labor • 90 days limited on lamp • two years of ProXchange replacement service

UltraLight DX3 Set Up

Position the UltraLight DX3 anywhere in the room.



Connect one computer and mouse source.



Adjust the power zoom and focus for large, vibrant images.



Supports composite and S-video sources such as a DVD player or a VCR to project video with stereo audio.

ORDERING INFORMATION

Model Number

DX3 For worldwide use

Optional Accessories

CASE-002	Carry-on rolling soft case
CASE-172	Compact rolling hard case (checkable/shippable)
A650	50 inch portable tabletop screen
LAMP-023	120-watt UHP lamp

DX3 PROJECTION DISTANCES / IMAGE SIZES

Projection Distance		Image Size (Diagonal)			
		Minimum		Maximum	
3.6'	1.1 m	2.1'	0.6 m	2.6'	0.8 m
6.5'	2.0 m	3.8'	1.2 m	4.7'	1.4 m
13.1'	4.0 m	7.6'	2.3 m	9.4'	2.9 m
19.7'	6.0 m	11.4'	3.5 m	14.1'	4.3 m
26.2'	8.0 m	15.3'	4.7 m	18.7'	5.7 m
32.8'	10.0 m	19.1'	5.8 m	23.4'	7.1 m

MOBILE/ULTRALIGHT

proxima®

www.proxima.com
1.888.PROXIMA

PRESENTATION SOLUTIONS

UltraLight Projectors

ULTRALIGHT DX3

proxima®
Own your audience.

Main Office: 9440 Carroll Park Drive, San Diego, CA 92121-2298
(858) 457-5500, FAX (858) 457-9647, (800) 447-7692 (U.S. and Canada)

European Office: K.G. Meldahlsvei 9, Postboks 1403
N-1602 Fredrikstad, Norway, [tel] +47 69 34 01 55, [fax] +47 69 34 06 32

www.proxima.com
www.presentersuniversity.com

Proxima and Proxima UltraLight are registered trademarks and ProXchange is a trademark of Proxima Corporation.
Other trademarks are property of their respective owners. ©2000 Proxima Corporation.
All rights reserved. Specifications are subject to change without notice.
6/00 709-00819-2 DX3 data sheet.qxd