

SIM2 EV 150



SIM2 EV 150



1 x DLP Chip
SVGA 4/3 Ti Digital Light Processing Chip

Display Type		
Ansi-Lumen	-	50 Lux (bei 203 cm Screen)
Contrast	500:1 full on/off	-
Black Level	-	-
Offset	-	-
Resolution	SVGA 800 x 600 480.000 Pixel	
Video Modes	XGA 1024 x 768 compressed PAL B, G, H, I, M, N, 60, SECAM, NTSC 3.58 & 4.43 automatically selected.	
Application	Standard-Portabel External training and company presentations, as well as product presentations. Very narrow picture width and rooms with very little light.	
Light Source	120W UHP Lamp Articel Nr.: Z930100290	
Light Life	6000 h.	
Operating Costs	-	
Focus	Powered	
Zoom	Powered 1,4	
Objective	-	
Throw Ratio	-	
Audio	0,5W Mono	
Connections	1 Composite video via RCA connectors 1 S-VHS via mini Din 4 pin 1 RGBHV via Dsub 15 (PC input) 1 x RGBS/YCrCbS via 4xRCA connectors 1 x RS232 on Dsub 9 pins Stecker 1 x jack 12V power output, active when the projector is ON	
Ceiling Mounting	Yes	
Power	170W max.	
Size WxHxD	350 x 167 x 318 mm (13,8"x6,6"x12,5") 18,59 L/dm³	
Operating Noise	-	
Weight	5,00 kg / 11,02 lbs.	
Keystone	Vert.: +/-17°	
Illumination	-	
Frequenz	H-sync: 15-80 kHz V-sync: 48-100 Hz	
Foot-Lamberts	-	
Features	■ De-interlacer	
Optional	Bulb only Philips Lamp original	
	NLMP3794	Z930100290 / 390

Order here: <https://www.hcinema.de/lampen/shop-en.php?id=n3794>
- Discontinued (EOL) // Last update of the data: 2023-08-04

Status
Data



More Details

HCinema

<https://www.projector-database.com/pro/sim2ev150-en.html>

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.