

SIM2 SDV 100



SIM2 SDV 100



Display Type	1 x DLP Chip SVGA 4/3 Ti Digital Light Processing Chip	
Ansi-Lumen	-	50 Lux (bei 203 cm Screen)
Contrast	500:1 full on/off	-
Black Level	-	-
Offset	-	-
Resolution	SVGA 800 x 600 480.000 Pixel XGA 1024 x 768 compressed	
Video Modes	NTSC, PAL, SECAM Pal 60 NTSC 4,43	
Application	Standard-Portabel External training and company presentations, as well as product presentations. Very narrow picture width and rooms with very little light.	
Light Source	150W UHP Lamp Articel Nr.: SDV100	
Light Life	2000 h.	
Operating Costs	-	
Focus	Powered	
Zoom	Powered 1,5	
Objective	-	
Throw Ratio	-	
Audio	10W	
Connections	Composite Video: RCA S-Video: 4 pin Mini DIN Data: 15-pin Mini D-Sub Audio: 2x RCA stereo Control: Serial (RS232C)	
Ceiling Mounting	Yes	
Power	210W	
Size WxHxD	225 x 130 x 335 mm (8,9"x5,1"x13,2") 9,8 L/dm³	
Operating Noise	-	
Weight	4,50 kg / 9,92 lbs.	
Keystone	Vertical	
Illumination	-	
Frequenz	H-sync: 15-60 kHz V-sync: 48-85 Hz	
Foot-Lamberts	-	
Features	-	
Status	- Discontinued (EOL) // Last update of the data: 2023-08-04	
Data		



More Details

HCinema

<https://www.projector-database.com/pro/sim2sdv100-en.html>

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.