

SPECKTRON

WXL-4000i Ultra-Short Throw Interactive Projector



- Ultra-Short Throw
- High Brightness(4000 lumens)
- WXGA resolution (1280 x 800)
- DLP Technology
- Large Projection sizes (80" ~ 110")
- Interactive

BRIGHTNESS



**BRIGHT
PROJECTION
ULTRA
SHORT THROW**



WXL-4000i

Native Resolution	WXGA (1280 x 800)
Aspect Ratio	16:10
Brightness	4000 Lumens
Light Source	Lamp (260W UHP)
Contract Ratio	10,000:1 (Dynamic)
Source Lifetime	4000/6000 ECO
Throw Ratio	0.27
Image Size	80" ~ 110"
Corner Keystone	Yes
Uniformity JBMA (typ)	80%
Projection Lens	WA21, Fix zoom lens
Dimension (mm)	383 x 310 x 86
Weight (Net Kgs)	5
Power Consumption (Normal)	320W
Power Consumption (Eco)	270W
Standby Power Consumption	Normal Standby: < AC 0.5W
Operation Temperature	+5 ~ +40°C
I/O Interface	VGA in x 1, VGA out x 1, HDMI x 2, Composite x 1, RJ45 x 1, Audio in-RCA (L/R) x 2, Audio in-3.5mm jack x1, Audio out x 1, Microphone x 1, Mini USB x 1, RS232 D-Sub 9pin x 1, Light Curtain x 1, USB A x 1
No. of Colors	1.07B (R/G/B 10 bit)
Speakers	10W x 1
Digital Keystone	± 10° Vertical and Horizontal
Interactive	Yes
Control	Yes (RJ45), RS232

