

XL 530U

Multimedia Projector

Business & Education



The Specktron XL 530U offers first rate performance with outstanding image quality powered by 3000 ANSI lumens. The device is loaded with features including keystone correction and high speed power off-for quick and easy use. Additionally it features a contrast ratio of 10,000:1, displaying sharp details and content. These features and more are all packed into a light weight, compact design making it easy to deliver on-site presentations, anywhere.

| KEY FEATURES   |                                                                 |
|----------------|-----------------------------------------------------------------|
| Technology     | 3LCD                                                            |
| Brightness     | 3000 Ansi Lumens                                                |
| Resolution     | XGA (1024 x768)                                                 |
| Contrast Ratio | 10,000:1                                                        |
| Lamp Life      | 5000 hrs (Normal)<br>6000 hrs (Economy)<br>8000 hrs (Super Eco) |
| Weight         | 2.887 kg                                                        |
| HDMI Support   | Yes                                                             |
| LAN            | Yes                                                             |
| USB (A)        | Yes                                                             |

## SPECIFICATIONS

|                             |                                                                                                                                                                                                                                          |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Display Technology          | 3LCD                                                                                                                                                                                                                                     |
| Display Panel               | 3 x 0.63"                                                                                                                                                                                                                                |
| Brightness                  | 3000 ANSI lumens                                                                                                                                                                                                                         |
| Native Resolution           | XGA (1024 x 768)                                                                                                                                                                                                                         |
| Contrast Ratio              | 10,000:1                                                                                                                                                                                                                                 |
| Lens                        | F=2.1-2.25, f=19.109-22.936 mm                                                                                                                                                                                                           |
| Uniformity                  | 80%                                                                                                                                                                                                                                      |
| Throw Ratio                 | 70" @ 2.1m                                                                                                                                                                                                                               |
| Image Size / Throw Distance | 0.887-10.899 m (30"-300")                                                                                                                                                                                                                |
| Aspect Ratio                | 4:3 (standard), 16:9 (Compatible)                                                                                                                                                                                                        |
| Keystone                    | Vertical: $\pm 30^\circ$ (Auto+ Manual), Horizontal: $\pm 15^\circ$ (manual), Pincushion/Barrel Correction: $\pm 40^\circ$ (Manual)                                                                                                      |
| Input                       | VGA*2; YCbCr/ Component (share with VGA port); Video*1; S-video (Share with VGA port); Audio-In (mini-jack, 3.5mm)*1; HDMI*1; Audio-In (L/R)-RCA*2, USB-A (JPEG reader)*1, USB-B*1 (display)                                             |
| Output                      | *1 (Share with VGA in 2), Audio Out (Mini-jack, 3.5 mm)*1                                                                                                                                                                                |
| Control                     | RS 232*1, USB-B*1 (Share with USB-B in), RJ 45*1                                                                                                                                                                                         |
| Speakers                    | 10W*1                                                                                                                                                                                                                                    |
| PC Compatibility            | VGA, SVGA, XGA, SXGA, WXGA, UXGA, Mac                                                                                                                                                                                                    |
| Video Compatibility         | PAL, SECAM, NTSC 4.43, PAL-M, PAL-N, 480i, 480p, 576i, 576p, 720p, 1080p, and 1080i                                                                                                                                                      |
| Lens Shift Horizontal       | N/A                                                                                                                                                                                                                                      |
| Lens Shift Vertical         | N/A                                                                                                                                                                                                                                      |
| Lamp                        | USHIO 230W                                                                                                                                                                                                                               |
| Lamp Life                   | 5000 hrs (Normal), 6000 hrs (Economy), 8000 hrs (Super Eco)                                                                                                                                                                              |
| Remote Control              | Yes                                                                                                                                                                                                                                      |
| Horizontal Frequency        | 15 ~ 100 kHz                                                                                                                                                                                                                             |
| Vertical Frequency          | 48 ~ 85 Hz                                                                                                                                                                                                                               |
| Standby Power               | <0.5W                                                                                                                                                                                                                                    |
| Power Consumption           | Max 310W (90V)                                                                                                                                                                                                                           |
| Power Supply                | 100V~240V @ 50-60 HZ                                                                                                                                                                                                                     |
| Operating Temp              | 5°C to 40°C (Over 35°C, go to Eco mode)                                                                                                                                                                                                  |
| Store Temp                  | -10°C to 60°C                                                                                                                                                                                                                            |
| Dimensions                  | 335mmX250mmX87mm                                                                                                                                                                                                                         |
| Weight                      | 2.887 kg.                                                                                                                                                                                                                                |
| OSD Languages               | English / German / French / Italian / Spanish / Polish / Swedish / Dutch / Portugese / Japanese / Simplified chinese / Korea / Russian / Arabic / Turkish / Finnish / Norwegian / Danish / Hungarian / Czech / Kazak / Vietnamese / Thai |
| Accessories Included        | User Manual (CD), Power Cord, Remote Control & battery, VGA Cable, Warranty Card.                                                                                                                                                        |